

InvisiLED® Pro 2

24V LED Tape Light

WAC LIGHTING

Responsible Lighting®



Tape Section



5 LED "L" Connector

Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Professional grade white tape light that delivers optimal color consistency and brightness. An ideal system for task or accent lighting applications.

FEATURES


- Ultra thin profile at 1/8"
- Diodes spaced evenly at 1" on center
- Minimum run length of 1'
- May be field cut every 6" at the end of a run
- 80,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

- Construction:** Flexible, silicone cased tape light. Peel and stick 3M construction adhesive on back. Indicating marks on back for field cutting.
- Power Supply:** Remote and plug-in electronic Class 2 transformers
120VAC 50/60Hz input, 24V 60W and 96W output
- Light Source:** 12 LEDs per foot
- Dimming:** May be dimmed with electronic low voltage (ELV) dimmer.
- Operating Temp:** -4°F – 122°F (-20°C – 50°C) at relative humidity 95%
- Standards:** CEC Title 24 (See below for list of models)
UL & CUL Listed for damp locations.

ORDER NUMBER – TAPE SECTION

Model	Watts/ft	Color Temp	CRI	Lumens/ft	Title 24	Length	Qty	Tape Color
LED-TX24	4	22 2200K	90	215	Yes	6IN 6 inches	1	WT White
		27 2700K	90	325	Yes	1 1 foot	1	
		30 3000K	90	300	Yes	1-40 1 foot	40	
		35 3500K	90	330	Yes	5 5 feet	1	
		45 4500K	85	330	No			




LED-TX24___ - ___-WT

Example: LED-TX2445-1-40-WT

ORDER NUMBER – 5 LED "L" CONNECTOR

Model	Watts	Color Temp	CRI	Lumens	Title 24	Tape Color
LED-TX24	2	22 2200K	90	90	Yes	5L-WT White
		27 2700K	90	130	Yes	
		30 3000K	90	130	Yes	
		35 3500K	90	135	Yes	
		45 4500K	85	135	No	



LED-TX24___-5L-WT

Example: LED-TX2435-5L-WT

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

InvisiLED® Pro 2

24V LED Tape Light

Class 2 Power Supply (Required)

Type		Model	Input	Output	Max Run	Dim	
Remote		EN-2460-RB2-T EN-24100-RB2-T	120VAC 120VAC	24VAC / 60W 24VAC / 96W	15 feet 25 feet	Yes Yes	<i>Includes a 6 foot lead wire</i>
Plug-in		EN-2460-P-AR-T EN-24100-P-AR-T	120VAC 120VAC	24VAC / 60W 24VAC / 96W	15 feet 25 feet	Yes Yes	<i>Includes a 6 foot lead wire</i>
Remote 277V		EN-24100-277-RB2-T	277VAC	24VDC / 96W	25 feet	No	<i>Includes a 6 foot lead wire</i>

Accessories

Aluminum Channel		LED-T-CH	5 feet	<i>Includes a diffuser, two end caps, and five screws</i>
Deep Aluminum Channel		LED-T-CH1	5 feet	<i>Includes a diffuser, two end caps, and five screws</i>
45° Angled Aluminum Channel		LED-T-CH2	5 feet	<i>Includes a diffuser, two end caps, and five screws</i>
Fixed Angle Channel Clip		LED-T-CL3-PT	5 feet	<i>Used to mount any aluminum channel Includes 2 pieces, 4 screws</i>
Adjustable Channel Clip		LED-T-CL2-PT	5 feet	<i>Used to mount any aluminum channel Adjusts 50° from center either way Includes 2 pieces, 4 screws</i>
Retrofit Channel		LED-T-RC	3 feet	<i>Creates fixed curves</i>
Clip		LED-T-CL	10 pcs	<i>Holds the tape from the underside Includes 10 pieces, 10 screws</i>
Curve Clip		LED-T-CL1	10 pcs	<i>Runs over the tape to secure the angled tape Includes 2 pieces, 4 screws</i>

Lead Wire		LED-TC-P-2 LED-TC-P-12	2 ft 12 ft	<i>Alternative lengths for plug-in power supplies</i>
Extension Cable		LED-TC-EXT-144	12 ft	<i>Extends distance between a hard wired power supply or wiring box to a tape section</i>
Low Voltage Wiring Box With Feed		LED-TC-B-2	L: 1½ in W: ¾ in H: 7⁄8 in	<i>Neatly houses up to two wires with 2" female feed</i>
Low Voltage Wiring Box		LED-T-B	L: 1½ in W: ¾ in H: 7⁄8 in	<i>Neatly houses up to two wires</i>
Wiring Box With Switch		TB-S	L: 6¼ in W: 1½ in H: 1¼ in	<i>Use when spanning a large gap in a system layout without leaving exposed wiring</i>

Joiner Cable		LED-TC-IC2 LED-TC-IC6 LED-TC-IC12 LED-TC-IC36 LED-TC-IC72	2 in 6 in 12 in 36 in 72 in	<i>Connects tape sections</i>
3-Way "Y" Connector		LED-TC-Y		<i>Connects tape sections</i>
4-Way "X" Connector		LED-TC-X		<i>Connects tape sections</i>
"L" Connector		LED-TC-L		<i>Connects tape sections</i>
End cap		LED-TC-EC		<i>1 cut end cap 1 male end cap</i>